## XRATE LIQUID ON-OFFLOADING FLOW SOLUTIONS FLOW RATE METER

	Item	Requirement	Range		
General	1	Line size	1.5" to 30" and higher		
	2	Line Schedule	Aı	Any	
	3	Pipe Class	Any		
	4	Pipe Material	Carbon Steel, SS316, Duplex (others)		
	5	Hazardous Area Protection	Atex, IECEx Zone 1 and 2		
	6	Ingress Protection	IP 66 (higher on request)		
Process Conditions	7	Fluid	Hydrocarbon / Water / Liquid mixture		
	8	Phase	Liquid with or without gas (typically up to 20% GVF)		
	9	Corrosive / Erosive	Can handle both due to clamp-on design		
	10	Case	Min Max		
	11	Flowrate m/s	0.1	40	
	12	Density	No limit	No limit	
	13	Design pressure	No limit	No limit	
	14	Design Temperature	-20 deg C	100 deg C (higher as option)	
	15	Viscosity	Range from water to heavy bunker oil		
Sensor	16	Sensor Type	Ultrasonic non-intrusive (clamp-on type).		
			Up to six pars (redundancy)		
	17	Measurement Principle	Ultrasonic Guided Wave Transit Time & Time Of Flight and Doppler		
	18	Housing Sensor Material	SS316 / Aluminium		
	19	Cable from sensor to transmitter	Armored, flame retardant typ (xx meters length)		
	20	Uncertainty	+/- 2% of flow at 0 gas and +/-5% up to 10% GVF (add +/-0,01 m/s)		
	21	Turndown ratio	400:1		
	22	Removable Assembly	Yes		
	23	Electrical Connection	4-20mA / Modbus (WiFi, Canbus, Profibus and other on request)		
	24	Upstream Straight Length	2-5D (target)		
	25	Downstream Straight Length	2-5D (target)		
	26	Flow Straighteners	Not required		
	27	Static Mixer	Not required		
Transmitter	28	Housing Material	SS316 / Aluminium		
	29	Calibration	0 - 100%		
	30	Electrical Connection	To custom specifications		
	31	Power Supply	12-24 VDC (external power, or other).		
			Typical 9,5Watt, 11 watt at start up		
	32	Output Signal	Modbus serial connected to flow computer via RS-485 /4-20mA		
			(others on request)		
	33	Mounting	Integrated in sensor		
Options	34	Pressure Transmitter	NA		
	35	Temperature Transmitter	2*PT 100 elements included		
	36	Flow Computer	NA		
	37	Local Display	Optional		
	38	Mounting Kit	Included		
	39	Weight	From 25 kg to 150 kg depending on size		
	40	Dimensions	See GA drawings from Xsens		
· · · · · · · · · · · · · · · · · · ·					



WWW.XSENSFLOW.COM

XSENS AS Godviksvingene 127 5179 Godvik NORWAY